


APPLICATION

CaRol™ TS250M winches are lifting equipment. They meet the requirements of lifting winches with a maximum load of 250 kg (directive 2006/42 / EEC)


They come with a davimast console equipped with a small boom and a return pulley

The console is equipped with a 150kg PPE anchor point in accordance with EN795A / 2012



TECHNICAL CHARACTERISTICS

- The caRol™ TS250M winches are delivered with an anchoring console that attaches to the mast of the davimast manufactured by Tractel®
- They are delivered with cable and connector
- They come in two capacities: 20m and 30m
- Drum and gear wheel mounted on bronze bearing
- Double braking safety by the self-braking wheel and screw system and the addition of a ratchet brake with doubled spring
- Rigid frame with painted mechanical parts and drum
- Easily accessible lever release drum with safety device preventing any release under load
- Protection of users and mechanical components by an ergonomic and removable protective cover for maintenance
- Quick and easy cable tie
- Variable length control crank (6 adjustment positions) allowing the user either a maximum control force or a quick maneuver for small loads or rewinding operation
- Self-locking crank adjustment button for maximum comfort and safety in use and allows the crank to be adjusted or removed to block the operation of the winch.
- The caRol™ TS250M winch with its console is fixed with 2 pins on the mast of the davimast
- Easily transportable thanks to the cross bar
- Equipped with a mounting console for davitrac



WLL	Cable			Force on handle (1)	handle (2)	weight (without cable)
	Ø	Capacity Max	Nombre de couches			
250 kg	5 mm	20 m	5	10 kg	21 mm	11 kg
250 kg	5 mm	30 m	5	13,5 kg	17 mm	17 kg

DESIGNATION	Code	HT	LG	EP	Weight without Console and cable	Weight with console + cable
caRol™ TS 250M with console davimast et câble de 20m	293799	250	225mm	190mm	11.6kg	26.5kg
caRol™ TS 250M with console davimast et câble de 30m	293809	280	240mm	200mm	17kg	20.5kg

DESCRIPTION

The caRol™ TS250M winches are lifting winches that have been tested to be attached to the mast of the Tractel® davimast. They are delivered with a fixing bracket specially dedicated for this use.

NORMS

It complies with:

- **EN 795A /2012** : PPE anchor
- **TS16415** : 150 kg
- **2006/42/CEE** : Winch conform to the machine directive
- **EN13157 :12/2004** Winch having undergone all breakage and endurance tests.

CODES

Product Description	Code
caRol™ TS 250M avec console davimast et câble de 20m	293799
caRol™ TS 250M avec console davimast et câble de 30m	293809
Options :	
Mat de base davimast	210188